

UPF10P-2S-H5-L-D0

Thermal detector for laser power measurement up to 2 W.



PRODUCT FAMILY KEY FEATURES

LOW POWER THERMOPILE

Noise level of a photo detector with the large bandwidth and high power capacity of a thermal device

IR FILTER (UPF10 MODELS)

Removes unwanted IR interference

HIGH PERFORMANCE

- Fast rise time (1.4 sec)
- High damage threshold (36 kW/cm²)

COMPACT DESIGN

Only 13 mm thick (UP10P model)

ENERGY MODE

Measure single shot energy up to $3\,\mathrm{J}$

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

STAND-S-233

SPECIFICATIONS

MEASUREMENT CAPABILITIES

| Maximum average power (continuous) | 2 W |
|--|---------------|
| Noise equivalent power ¹ | 30 µW |
| Spectral range ² | 0.28 - 2.1 μm |
| Typical rise time ³ | 1.4 s |
| Power calibration uncertainty ⁴ | ±2.5 % |
| Repeatability | ±0.5 % |

- 1. Nominal value, actual value depends on electrical noise in the measurement system.
- 2. For the calibrated spectral range, see the user manual.
- 3. With anticipation.
- 4. Including linearity with power.

MEASUREMENT CAPABILITIES (ENERGY MODE)

| Maximum measurable energy ¹ | 3 J |
|---|-------|
| Noise equivalent energy ² | 5 mJ |
| Minimum repetition period | 2 s |
| Maximum pulse width | 63 ms |
| Energy calibration uncertainty ³ | +5 % |

- 1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).
- 2. Nominal value, actual value depends on electrical noise in the measurement system.
- 3. When single-shot energy calibration is purchased

DAMAGE THRESHOLDS

| Maximum average power density ¹ | 36 kW/cm² |
|--|-----------|
| | |

Maximum energy density²

- 1. At 1064 nm, 10 W CW. May vary with wavelength and average power.
- 2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Convection

| Aperture diameter | 10 mm |
|-----------------------|----------------------|
| Absorber | H5 |
| Dimensions | 46H x 46W x 21.4D mm |
| Weight | 0.14 kg |
| ORDERING INFORMATION | |
| UPF10P-2S-H5-L-D0 | |
| UPF10P-2S-H5-L-INT-D0 | |
| UPF10P-2S-H5-L-IDR-D0 | |

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?



Find your local sales representative at gentec-eo.com/contact-us