

S-LINK-1

PC interface for power & energy measurement. Single-channel, USB output.



KEY FEATURES

READS BOTH POWER AND ENERGY

Thermopiles and pyroelectrics

AVAILABLE WITH 1 OR 2 CHANNELS

S-LINK-1 and S-LINK-2 models now available

PC-BASED

Connects to your PC with included software

SERIAL COMMANDS

Serial commands are available on all versions to let you take full control

FASTEST DATA TRANSFER RATE

Get all the points transferred directly into your PC at 10 kHz/Channel

USB OR ETHERNET

Choose your favourite communications port. The USB version is port-powered

repetition rate and average power

EXTERNAL TRIGGER

Every model comes standard with a 2.4 V to 24 V external trigger

SPECIFICATIONS

CONTROLLER AND GUI SPECIFICATIONS	
Digital display size	Computer screen
Data display	Real time, ratio, line plot, histogram, statistics and 3D histogram
External trigger	3-24 V @ 13 mA, optically isolated
Serial commands via	USB
POWER METER SPECIFICATIONS	
Power range	1 µW - 10 kW
Device accuracy	±0.75 % for 10 % to full scale
Statistics	Current value, max, min, average, standard deviation, RMS & PTP stability, time
Response time	1s
ENERGY METER SPECIFICATIONS	
Energy range	8 fJ to 20 kJ
Digital resolution	Normal Mode: Current scale/4096
Device accuracy	±1 % (<500 Hz) ±2 % (500 Hz - 1.2 kHz) ±3 % (1.2 - 6 kHz) ±6 % (6 - 10 kHz)
Repetition rate ¹	10 kHz
Real-time data transfer ²	10 kHz/Channel in normal mode, no missing point
Statistics	Current value, max, min, average, standard deviation, RMS & PTP stability, pulse #,

- 1. Maximum repetition rate may vary with PC and detector speeds.
- 2. Actual rate may depend on the computer

PHYSICAL CHARACTERISTICS

Dimensions 106W x 34H x 147D mm

Weight 0.424 kg

S-LINK-1 202225

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us