

THZ5B-BL-DA-D0

MEASUREMENT CAPABILITIES

THz detector for power measurements up to 25 μ W.



PRODUCT FAMILY KEY FEATURES

RELATIVE MEASUREMENTS FROM 0.1 TO 30 THZ

Broadband, room temperature operation, easier to use and less expensive than a Golay $\ensuremath{\mathsf{cell}}$

WIDE DYNAMIC RANGE FROM NW TO MW

With state of the art pyroelectric sensors, measure down to 50 nW with 1 nW resolution.

SEVERAL SENSOR SIZES AVAILABLE

Choice of 5 mm and 9 mm diameter

CALIBRATED AT 0.63 MM

THZ-B detectors are calibrated at a single wavelength (0.63 $\mu m)$ and include typical wavelength correction data from 0.25 to 440 μm . They are used for relative measurements outside that range.

SDC-500 OPTICAL CHOPPER

All THZ-B detectors require the use of an optical chopper, like our SDC-500, to sync the signal at either 5 Hz (DA models) or 25 Hz (DZ models).

COMPATIBLE STAND

STAND-D-233

SPECIFICATIONS

Maximum average power	25 μW
Noise equivalent power	1 nW
Spectral range ¹	10 - 3000 μm
Frequency ²	0.1 - 30 THz
Typical rise time	0.2 s
Typical power sensitivity	140 kV/W
Chopping frequency ³	5 Hz
Minimum repetition rate	1000 Hz
 Projected spectral range. From 10 to 440 μm, spectrometer measurement. From 440 to 3000 μm, relative measurement only. This spectr Projected spectral range. From 10 to 440 μm, spectrometer measurement. From 440 to 3000 μm, relative measurement only. This spectr SDC-500 digital optical chopper sold separately DAMAGE THRESHOLDS	ral range is subject to change.
Maximum average power density PHYSICAL CHARACTERISTICS	0.01 W/cm ²
Aperture diameter	5 mm
Absorber	BL
Dimensions	66.0Ø x 46.5D mm
Weight	0.23 kg
ORDERING INFORMATION	
THZ5B-BL-DA-D0	

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us