

QS5-IL

Hybrid pyroelectric sensor with metallic coating. Low noise level.



PRODUCT FAMILY KEY FEATURES

BROAD SPECTRAL RESPONSE

From 0.1 to 1000 μm

3 FAMILIES OF PRODUCTS TO CHOOSE FROM:

- QS-L: discrete pyro detectors, low noise level
- QS-H: discrete pyro detectors, high average power
- QS-IL: hybrid pyro detectors, current mode, low noise level

EASY TO INTEGRATE FORMAT

TO5 and TO8 packages make the QS-H detectors small and easy to integrate in an existing system.

LARGE AREA SENSORS

5 mm and 9 mm diameter pyroelectric sensors make optical alignment easier.

SEVERAL IR WINDOWS IN OPTION

- Quartz: 0.2 – 3.5 μm
- Barium fluoride: 0.2 – 17.5 μm
- Sapphire: 0.1 – 7.0 μm
- Silicon: 1.2 – 9.0 μm and 22 – 100 μm
- AR germanium: 1.8 – 23 μm (10.6 μm peak)



SPECIFICATIONS

MEASUREMENT CAPABILITIES

Maximum average power	50 mW
Noise equivalent power ¹	6 nW
Spectral range	0.1 - 1000 μm
Current responsivity	0.25 $\mu\text{A/W}$
Thermal frequency	0.5 Hz
Voltage responsivity ²	13 kV/W
Feedback resistor	100 G Ω
Supply voltage	± 5 V

1. 630 nm, 5 Hz, 1 Hz bandwidth
2. 630 nm, 15 Hz

PHYSICAL CHARACTERISTICS

Aperture diameter	5 mm
Absorber	MT
Dimensions	9.1 \varnothing x 6.4D mm
Weight	0.001 kg
Package	TO5

ORDERING INFORMATION

QS5-IL	201687
--------	--------

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us