


QE145LP-H-MB-QED-D0

Pyroelectric detector for laser energy measurement up to 385 J.



PRODUCT FAMILY KEY FEATURES

CUSTOM-BUILT

Contact us with your requirements for a version tailored to your needs

MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

EXTRA LARGE APERTURE

Effective aperture of 145 mm \varnothing

QED ATTENUATOR AVAILABLE

Measure up to 5X higher energies. Available with optional calibration, all wavelengths between 532 & 1064 nm, or single wavelength. [Read more.](#)

TEST TARGET INCLUDED

With the MB models

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

[STAND-D-443](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Spectral range ¹	0.3 - 2.1 μm
Repeatability	<0.5%
Maximum repetition frequency	200 Hz
Maximum measurable energy ²	385 J
Noise equivalent energy ³	200 μJ
Maximum pulse width	5 ms
Energy calibration uncertainty	$\pm 3\%$

1. For the calibrated spectral range, see the user manual.
2. These products are custom-built. Contact us with your requirements for a version tailored to your needs.
3. Nominal value. Actual value depends on electrical noise in the measurement system.

DAMAGE THRESHOLDS

Maximum average power density ¹	600 W/cm ²
Maximum energy density ²	8 J/cm ²
Maximum power	190 W

1. May vary with wavelength and average power.
2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Cooling	Convection (heatsink)
Aperture diameter	135 mm
Absorber	QED
Dimensions	180H x 180W x 107D mm
Weight	2.8 kg

ORDERING INFORMATION

QE145LP-H-MB-QED-D0
QE145LP-H-MB-QED-INT-D0
QE145LP-H-MB-QED-INE-D0

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us