

## UV CONVERTERS (BSF)

BEAMAGE용 UV 컨버터: 23mm 구경, 다양한 수정 사용가능.



### 제품군 주요 특징

#### CONVERT UV LIGHT TO VISIBLE

The BSF series transforms wavelengths contained between X-rays and 400 nm to visible and near-IR wavelengths.

#### IMAGE LARGER BEAMS

The magnification properties allow you to image beams that are larger than the sensor.

#### CONTROL THE EXPOSURE

Built with an iris at the output port for a control of the exposure on the CMOS sensor.

#### READY TO USE WITHIN MINUTES

Removable extension tube that is easily fixed onto the entrance port of the BEAMAGE camera.

### 사양

계측 성능	
스펙트럼 범위	10 - 535 nm
최대 빔 사이즈	23 mm Ø
픽셀 증배율(PMF)	1.4
최소 계측가능 빔	79 µm
최대 반복률	Depends on crystal type: from 25 Hz to 1 MHz
손상 한계	
물리적 특성	
치수	35Ø X 97D mm
중량	0.21 kg
구경 해제	23 mm
주문 정보	
UV CONVERTERS (BSF)	UVC

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

### 이 제품에 관심이 있으십니까?

견적받기

gentec-eo.com/ko/contact-us에서 현지 영업 담당자를 찾으십시오.