UP10K-2S-H5-L-D0

최대2 W의 레이저 파워 계측용 열 검출기.

제품군 주요 특징

LOW POWER THERMOPILE

Noise level of a photo detector with the large bandwidth and high power capacity of a thermal device

IR FILTER (UPF10 MODELS)

Removes unwanted IR interference

HIGH PERFORMANCE

- Fast rise time (1.1 sec)
- High damage threshold (36 kW/cm^2)

COMPACT DESIGN

Only 13 mm thick (UP10P model)

ENERGY MODE

Measure single shot energy up to 3 J

SMART INTERFACE

Containing all the calibration data

호환 스탠드

STAND-S-233

사양

계측 성능

최대 평균 파워(연속)	2 W
등가노이즈파워(NEP)[1]	30 µW
스펙트럼 범위[2]	0.193 - 20 µm
일반 상승 시간[3]	1.1 s
파워 교정 불확정성[4]	±2.5 %
반복성	±0.5 %

1. 액면 값. 실제 값은 측정 시스템의 전기적 노이즈에 따라 달라집니다.
2. 교정된 스펙트럼 범위는 사용설명서를 참조하십시오.
3. 기대치.
4. 출력에 선형성이 포함됩니다.

측정 기능 (에너지 모드)

최대 계측가능 에너지[1]	3 J
등가노이즈에너지[2]	5 mJ
최소 반복 기간	2 s
최대 펄스폭	63 ms
에너지 교정 불확정성[3]	±5 %

1. 360µs 펄스의 경우. 긴 펄스(ms)에는 더 높은 펄스 에너지가 가능하고 짧은 펄스(ns)에는 적은 에너지가 가능합니다.
2. 액면 값. 실제 값은 측정 시스템의 전기적 노이즈에 따라 달라집니다.
3. 단발성 에너지 교정을 구매할 경우

손상 한계

최대 평균 파워 밀도[1]	36 kW/cm²
최대 에너지 밀도[2]	1 J/cm²

1. 1064nm, 10W CW. May vary with wavelength and average power.
2. 1064nm, 7ns, 10Hz. May vary with wavelength and pulse width.

물리적 특성

냉각	대류

구경 지름	10 mm
업소버	H5
치수	50H x 50W x 21.5D mm
중량	0.193 kg

주문 정보

UP10K-2S-H5-L-D0	202872
UP10K-2S-H5-L-IDR-D0	203317
UP10K-2S-H5-L-INT-D0	203035

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

이 제품에 관심이 있으십니까?

견적받기

gentec-eo.com/ko/contact-us에서 현지 영업 담당자를 찾으십시오.