

UP55N-50H-W9-D0

Thermal detector for laser power measurement up to 50 W.



PRODUCT FAMILY KEY FEATURES

MODULAR CONCEPT

Increase the power capability of your detector: 4 different cooling modules

VERY HIGH DAMAGE THRESHOLD

100 kW/cm² in average power density

VERY LARGE APERTURE

55 mm effective aperture diameter, perfect for the largest beams

HIGHEST ENERGY READINGS IN THE SERIES

Measure single shot energy up to 500 J

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

[STAND-S-443](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Maximum average power (continuous)	50 W
Maximum average power (1 minute)	85 W
Noise equivalent power ¹	5 mW
Spectral range ²	0.193 - 10 µm
Typical rise time ³	3.5 s
Power calibration uncertainty ⁴	±2.5 %
Repeatability	±0.5 %

1. Nominal value, actual value depends on electrical noise in the measurement system.

2. For the calibrated spectral range, see the user manual.

3. With anticipation.

4. Including linearity with power.

MEASUREMENT CAPABILITIES (ENERGY MODE)

Typical energy sensitivity	0.02 mV/J
Maximum measurable energy ¹	500 J
Noise equivalent energy ²	0.25 J
Minimum repetition period	11.1 s
Maximum pulse width	467 ms
Energy calibration uncertainty ³	±5 %

1. For 360 µs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).

2. Nominal value, actual value depends on electrical noise in the measurement system.

3. When single-shot energy calibration is purchased

DAMAGE THRESHOLDS

Maximum average power density ¹	100 kW/cm ²
Maximum energy density ²	1.1 J/cm ²

1. At 1064 nm, 10 W CW. May vary with wavelength and average power.

2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Cooling	Convection (heatsink)
Aperture diameter	55 mm
Absorber	W
Dimensions	89H x 89W x 109D mm
Weight	0.93 kg
ORDERING INFORMATION	
UP55N-50H-W9-D0	205344
UP55N-50H-W9-BLU-D0	205356
UP55N-50H-W9-IDR-D0	205354
UP55N-50H-W9-INT-D0	205348

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us