

## XLP12-3S-VP-D0

Thermopile detector for laser power measurement up to 3 W.



## PRODUCT FAMILY KEY FEATURES

## LOW POWER THERMOPILE

Noise level of a photo detector with the large bandwidth and high power capacity of a thermal device

#### MINIMAL THERMAL DRIFT

Only 6 µW/°C (with the IR filter)

#### HIGH SENSITIVITY

200 mV/W (without the IR filter)

## SPECIAL MODEL FOR ULTRASHORT PULSES

VP (volume absorber) version is perfect for low power lasers with ultrashort pulses (ps and fs)

Convection

0.32 kg

#### IR FILTER (XLPF12 MODEL)

Removes unwanted IR interference

#### **ISOLATION TUBE**

Eliminates power fluctuations created by air turbulence

## **COMPATIBLE STAND**

STAND-S-233

# **SPECIFICATIONS**

MEASUREMENT CAPABILITIES	
Maximum average power (continuous)	3 W
Maximum average power (1 minute)	3 W
Noise equivalent power <sup>1</sup>	0.5 µW
Spectral range <sup>2</sup>	0.25 - 20 μm
Typical rise time <sup>3</sup>	3 s
Power calibration uncertainty <sup>4</sup>	±2.5 %
Repeatability	±0.5 %
Thermal drift <sup>5</sup>	12 μW/°C

- 1. Nominal value, actual value depends on electrical noise in the measurement system.
- 2. For the calibrated spectral range, see the user manual.
- 3. With anticipation.
- 4. Including linearity with power.
- 5. With MAESTRO.

Cooling

Weight

## DAMAGE THRESHOLDS

Maximum average power density<sup>1</sup> 30 W/cm<sup>2</sup>

Maximum energy density<sup>2</sup> 4J/cm<sup>2</sup>

1. At 1064 nm, 1 W CW. May vary with wavelength and average power.

2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

## PHYSICAL CHARACTERISTICS

Aperture diameter	12 mm
Absorber	VP
Dimensions	73H x 73W x 20D mm (72D mm with tube)

ORDERING INFORMATION

XLPI2-3S-VP-D0 202227

XLP12-3S-VP-IDR-D0	203393
XLP12-3S-VP-BLU-D0	205135
XLP12-3S-VP-INT-D0	203031

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

# **INTERESTED IN THIS PRODUCT?**



Find your local sales representative at gentec-eo.com/contact-us