

UP25M-350W-H12-D0

Thermal detector for laser power measurement up to 350 W.



KEY FEATURES

MODULAR CONCEPT

Increase the power capability of your detector: 4 different cooling modules

HIGH PERFORMANCE

- Fast rise time (1.3 sec)
- High damage threshold (45 kW/cm²)

ENERGY MODE

Measure single shot energy up to 40 J

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

[STAND-S-443](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Maximum average power (continuous) ¹	350 W
Maximum average power (1 minute) ²	350 W
Noise equivalent power ³	10 mW
Spectral range ⁴	0.193 - 20 μm
Typical rise time ⁵	1.3 sec
Typical power sensitivity ⁶	0.1 mV/W
Power calibration uncertainty ⁷	±2.5 %
Repeatability	±0.5 %

1. Minimum cooling flow 1.5 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.
2. Minimum cooling flow 1.5 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.
3. Nominal value, actual value depends on electrical noise in the measurement system.
4. For the calibrated spectral range, see the user manual.
5. With anticipation.
6. Into 100 kΩ load. Maximum output voltage = sensitivity x maximum power.
7. Including linearity with power.

MEASUREMENT CAPABILITIES (ENERGY MODE)

Typical energy sensitivity	0.05 mV/J
Maximum measurable energy ¹	40 J
Noise equivalent energy ²	0.2 J
Minimum repetition period	11.5 s
Maximum pulse width	390 ms
Energy calibration uncertainty ³	±5 %

1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).
2. Nominal value, actual value depends on electrical noise in the measurement system.
3. When single-shot energy calibration is purchased

DAMAGE THRESHOLDS

Maximum average power density ¹	45 kW/cm ²
--	-----------------------

Maximum energy density²

1 J/cm²

1. At 1064 nm, 10 W CW.
2. At 1064 nm, 7 ns, 10 Hz.

PHYSICAL CHARACTERISTICS

Aperture diameter	25 mm
Absorber	H12
Dimensions	119H x 89W x 43D mm
Weight	0.87 kg

ORDERING INFORMATION

UP25M-350W-H12-D0	201893
UP25M-350W-H12-IDR-D0	203359
UP25M-350W-H12-BLU-D0	203664
UP25M-350W-H12-INT-D0	203051

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us