

QE95LP-H-MB-QED-D0

Pyroelectric detector for laser energy measurement up to 250 J.



KEY FEATURES

MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

EXTRA LARGE APERTURE

Effective aperture of 95 mm Ø

QED ATTENUATOR AVAILABLE

Measure up to 5X higher energies. Available with optional calibration, all wavelengths between 532 & 1064 nm, or single wavelength. [Read more.](#)

LOW NOISE LEVEL

15 µJ for the MB coating

TEST TARGET INCLUDED

With the MB models

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

[STAND-D-443](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Spectral range ¹	0.3 - 2.1 µm
Typical rise time	2 ms
Repeatability	<0.5%
Maximum repetition frequency	40 Hz
Typical energy sensitivity	2 V/J
Maximum measurable energy ²	250 J
Noise equivalent energy ³	30 µJ
Maximum pulse width	1.5 ms
Energy calibration uncertainty	±3 %

1. For the calibrated spectral range, see the user manual.

2. At 1064 nm, 7 ns, 10 Hz. Increasing pulse width increases maximum measurable energy.

3. Nominal value. Actual value depends on electrical noise in the measurement system.

DAMAGE THRESHOLDS

Maximum average power density ¹	600 W/cm ²
Maximum energy density ²	8 J/cm ²
Maximum power	90 W

1. At 1064 nm, 7 ns, 10 Hz.

2. At 1064 nm, 7 ns, 10 Hz.

PHYSICAL CHARACTERISTICS

Aperture diameter	90 mm
Absorber	QED
Dimensions	122H x 122W x 98D mm
Weight	1.2 kg

ORDERING INFORMATIONS

QE95LP-H-MB-QED-D0	202195
QE95LP-H-MB-QED-IDR-D0	

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us