

QE195LP-H-MB-D0

Pyroelectric detector for laser energy measurement up to 125 J.



PRODUCT FAMILY KEY FEATURES

CUSTOM-BUILT

[Contact us](#) with your requirements for a version tailored to your needs

MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

EXTRA LARGE APERTURE

Effective aperture of 195 mm Ø

QED ATTENUATOR AVAILABLE

Measure higher energy levels and with higher damage thresholds.
[Read more.](#)

TEST TARGET INCLUDED

With the MB models

SMART INTERFACE

Containing all the calibration data

AWARD-WINNING TECHNOLOGY

The QE195 series of laser energy detectors was recognized among the most innovative photonics technologies for the [2024 Laser Focus World Innovators Awards](#), as a Platinum honoree.



COMPATIBLE STAND

[STAND-D-233](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Spectral range ¹	0.193 - 20 µm
Repeatability	<0.5%
Maximum repetition frequency	40 Hz
Maximum measurable energy ²	125 J
Noise equivalent energy ³	500 µJ
Maximum pulse width	1 ms
Energy calibration uncertainty	±3 %

1. For the calibrated spectral range, see the user manual.

2. At 1064 nm, 7 ns, single-shot. Increasing pulse width increases maximum measurable energy. Limited by electronics, contact Gentec-EO for different specifications.

3. Nominal value. Actual value depends on electrical noise in the measurement system.

DAMAGE THRESHOLDS

Maximum average power density ¹	10 W/cm ²
Maximum energy density ²	0.6 J/cm ²
Maximum power	160 W

1. May vary with wavelength and average power.
2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Cooling	Convection (heatsink)
Aperture diameter	195 mm
Absorber	MB
Dimensions	229H x 229W x 103D mm
Weight	4.9 kg

ORDERING INFORMATION

QE195LP-H-MB-D0
QE195LP-H-MB-IDR-D0
QE195LP-H-MB-INE-D0
QE195LP-H-MB-INT-D0

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us