

UP55M-700W-HD-D0

Thermal detector for laser power measurement up to 700 W.



PRODUCT FAMILY KEY FEATURES

HIGH DENSITY ABSORBER

The HD absorber is the strongest on the market for use at high powers, presenting both high average power handling and high power density capabilities.

FAST AND COMPACT

A very compact detector that measures up to 700 W of continuous power.

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

[STAND-S-443](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

| | |
|---|--------------------------|
| Maximum average power (continuous) ¹ | 700 W |
| Maximum average power (1 minute) ² | 700 W |
| Noise equivalent power ³ | 45 mW |
| Spectral range ⁴ | 0.193 - 20 μm |
| Typical rise time ⁵ | 2.8 s |
| Power calibration uncertainty ⁶ | $\pm 2.5\%$ |
| Repeatability | $\pm 0.5\%$ |

1. Minimum cooling flow 1.5 liters/min, water temperature $\leq 22^\circ\text{C}$, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.

2. Minimum cooling flow 1.5 liters/min, water temperature $\leq 22^\circ\text{C}$, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.

3. Nominal value, actual value depends on electrical noise in the measurement system.

4. For the calibrated spectral range, see the user manual.

5. With anticipation.

6. Including linearity with power.

MEASUREMENT CAPABILITIES (ENERGY MODE)

| | |
|---|-----------|
| Maximum measurable energy ¹ | 200 J |
| Noise equivalent energy ² | 0.25 J |
| Minimum repetition period | 12 s |
| Maximum pulse width | 430 ms |
| Energy calibration uncertainty ³ | $\pm 5\%$ |

1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).

2. Nominal value, actual value depends on electrical noise in the measurement system.

3. When single-shot energy calibration is purchased

DAMAGE THRESHOLDS

| | |
|--|----------------------------|
| Maximum average power density ¹ | 45 kW/cm^2 |
| Maximum energy density ² | 1 J/cm^2 |

1. At 1064 nm, 10 W CW. May vary with wavelength and average power.

2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

| | |
|-------------------|---------------------|
| Cooling | Water |
| Aperture diameter | 55 mm |
| Absorber | HD |
| Dimensions | 119H x 89W x 43D mm |
| Weight | 0.9 kg |

ORDERING INFORMATION

| | |
|----------------------|--------|
| UP55M-700W-HD-D0 | 201908 |
| UP55M-700W-HD-INT-D0 | 203199 |
| UP55M-700W-HD-IDR-D0 | 205132 |
| UP55M-700W-HD-BLU-D0 | 203724 |

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us