

## UD25-350-H12

Uncalibrated thermal disk sensor for laser power measurement up to 350 W.



### KEY FEATURES

#### DESIGNED FOR INTEGRATION

With a broad bandwidth and high power densities

#### VERY THIN PROFILES

Starting at only 2 mm in thickness

#### VARIOUS APERTURE SIZES

Choose your aperture from 10 mm to 55 mm.

#### 2 LEVELS OF INTEGRATION

- Disk alone
- Disk + PCB



## SPECIFICATIONS

### MEASUREMENT CAPABILITIES

Maximum average power	350 W
Maximum average power (fan-cooled)	250 W
Noise equivalent power	10 mW
Spectral range	0.19 - 20 $\mu\text{m}$
Typical rise time <sup>1</sup>	7.9 s
Typical power sensitivity <sup>2</sup>	0.1 mV/W
Recommended load impedance	>100 k $\Omega$

1. These characteristics depend on the thermal management and electronics provided by the user. Packaging, cooling and electronics similar to our UP series detectors will provide similar performances. See UP series specifications sheets for more details. Actual performance depends on the tradeoffs in a user's design. It may be possible to enhance some performance parameters at the expense of others.

2. Without anticipation algorithm or circuitry.

### MEASUREMENT CAPABILITIES (ENERGY MODE)

Typical energy sensitivity	0.05 mV/J
Maximum measurable energy <sup>1</sup>	40 J
Noise equivalent energy	200 mJ

1. For 360  $\mu\text{s}$  pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).

### DAMAGE THRESHOLDS

Maximum average power density	45 kW/cm <sup>2</sup>
Maximum energy density <sup>1</sup>	1 J/cm <sup>2</sup>

1. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

### PHYSICAL CHARACTERISTICS

Aperture diameter	25 mm
Absorber	H12
Dimensions	54 $\varnothing$ x 3D mm
Weight	0.013 kg

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

## INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at [gentec-eo.com/contact-us](https://gentec-eo.com/contact-us)