

B3-IR-FILTER

Filtre IR pour la caméra BEAMAGE.



CARACTÉRISTIQUES CLÉS DE LA FAMILLE DE PRODUITS

IR LOW-PASS FILTER

The B3-IR-FILTER is a color glass filter specifically designed for IR applications. Acting as a low-pass filter, the B3-IR-FILTER cuts all the wavelengths below 1250 nm and only lets the IR wavelengths pass. It transmits approximately 70% of the incident light.

READY TO USE WITHIN MINUTES

The B3-IR-FILTER is SM1 threaded and comes with a SM1 to C-mount adaptor so you can mount it on the BEAMAGE camera.



SPÉCIFICATIONS

CAPACITÉS DE MESURE

Domaine spectral	1250 - 1350 nm
Parallélisme	< 3 arcmin
Puissance maximale	1 W
Qualité de surface	80-50 Rayure-Échignure
Planéité de surface	< $\lambda/4$
Épaisseur	6,3 mm

SEUILS DE DOMMAGE

Seuils de dommage	30 W/cm ²
-------------------	----------------------

CARACTÉRISTIQUES PHYSIQUES

Dimensions	30.5Ø X 11.4D mm
Poids	0,04 kg
Filetage de raccordement	SM1
Ouverture dégagée	80 % de la surface
Adaptateur compris	SM1 / C-Mount
Tolérance dimensionnelle	+0.0/-0.2 mm

INFORMATIONS DE COMMANDE

B3-IR-FILTER	202855
--------------	--------

INTÉRESSÉ PAR CE PRODUIT?

OBTENIR UNE SOUMISSION

