

P-LINK-4 (USB)

PC interface for power measurement. Four channels.



PRODUCT FAMILY KEY FEATURES

READS ALL POWER DETECTORS TYPES

Thermopiles and photo detectors of the PH100 & PH20 series

MULTI-CHANNEL CAPABILITIES

Available with 1 or 4 channels

PC-BASED

Connects to your PC with included software

SMALL SIZE

Only 91 mm (L) x 57 mm (W) x 36 (H)

SERIAL COMMANDS

Serial commands are available on both versions to let you take full control

REAL-TIME STATISTICAL FUNCTIONS

Max, min, average, standard deviation, RMS and PTP stability, pulse # and repetition rate

USB, RS-232 OR ETHERNET

Choose your favourite communications port. The USB version is port-powered. Ethernet available only on 4-channel version.

SPECIFICATIONS

CONTROLLER AND GUI SPECIFICATIONS

| | |
|-------------------------|---|
| Digital display size | Computer screen |
| Data display | Real time, ratio, line plot, histogram, statistics and 3D histogram |
| External trigger | None |
| Real-time data transfer | 10 Hz |
| Serial commands via | USB |

POWER METER SPECIFICATIONS

| | |
|-----------------|---|
| Device accuracy | ±0.5 % full scale |
| Statistics | Current value, max, min, average, standard deviation, RMS & PTP stability, time |
| Response time | Current value, max, min, average, standard deviation, RMS & PTP stability, time |

ENERGY METER SPECIFICATIONS

PHYSICAL CHARACTERISTICS

| | |
|------------|----------------------|
| Dimensions | 286W x 233H x 43D mm |
| Weight | 2.5 kg |

ORDERING INFORMATION

| | |
|----------------|--------|
| P-LINK-4 (USB) | 202223 |
|----------------|--------|

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us

