gentec-e
PARTNERS for ACCURACY

QE95LP-H-MB-D0

Pyroelectric detector for laser energy measurement up to 35 J.

PRODUCT FAMILY KEY FEATURES

MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

EXTRA LARGE APERTURE

Effective aperture of 95 mm Ø

QED ATTENUATOR AVAILABLE

Measure higher energy levels. Available with optional calibration, all wavelengths between 532 and 1064 nm, or single wavelength. Read more.

LOW NOISE LEVEL

15 µJ for the MB coating

TEST TARGET INCLUDED

With the MB models

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

STAND-D-443

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Spectral range[1]	0.193 - 20 µm
Typical rise time	2 ms
Repeatability	<0.5%
Maximum repetition frequency	40 Hz
Maximum measurable energy[2]	35 J
Noise equivalent energy[3]	15 µJ
Maximum pulse width	1.5 ms
Energy calibration uncertainty	±3 %

1. For the calibrated spectral range, see the user manual.
2. At 1064 nm, 7 ns, single-shot. Increasing pulse width increases maximum measurable energy.
3. Nominal value. Actual value depends on electrical noise in the measurement system.

DAMAGE THRESHOLDS

Maximum average power density[1]	10 W/cm²
Maximum energy density[2]	0.6 J/cm²
Maximum power	40 W

1. May vary with wavelength and average power.
2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

PHYSICAL CHARACTERISTICS

Cooling	Convection (heatsink)
Aperture diameter	95 mm
Absorber	MB
Dimensions	122H x 122W x 99D mm
Weight	1.2 kg

ORDERING INFORMATION

QE95LP-H-MB-D0	201309
QE95LP-H-MB-IDR-D0	203305

QE95LP-H-MB-INT-D0	202774
QE95LP-H-MB-INE-D0	

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us