

CAMERA LENSES

Camera lenses for BEAMAGE: 25 mm or 50 mm focal length.



PRODUCT FAMILY KEY FEATURES

MANAGE THE BEAM SIZE

A simple solution is offered to those who need to profile beams that are larger than the BEAMAGE sensor. This solution is a beam reducing optical component called CAMERA LENS.

IMAGE VERY LARGE BEAMS

The camera lenses in the CL series work by indirectly imaging the reflection or transmission of the beam after it has hit a diffusing element. For larger beams, simply increase the distance between the diffuser and the BEAMAGE.

READY TO USE WITHIN MINUTES

The CL series is C-mount threaded so you can mount it directly on the BEAMAGE camera.



SPECIFICATIONS

MEASUREMENT CAPABILITIES

| | |
|-----------------------------------|---|
| Focal length | 25 mm |
| Horizontal FOV | 14° / 7° |
| FOV at 1 m | 245 mm |
| Minimum working distance | 0.5 m |
| Maximum beam size | Limited by field of view |
| Inverted image | Yes |
| Pixel multiplication factor (PMF) | Depends on set-up, auto-calibration routine available in the software |
| Damage thresholds | Very high because of indirect measurement |

PHYSICAL CHARACTERISTICS

| | |
|-----------------|---------|
| Mounting thread | C-Mount |
|-----------------|---------|

ORDERING INFORMATION

| | |
|---------------|----|
| CAMERA LENSES | CL |
|---------------|----|

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us