

## UPI7P-6S-H5-D0

Thermal detector for laser power measurement up to 6 W.



### PRODUCT FAMILY KEY FEATURES

#### ULTRA THIN CASING

Only 10.7 mm thick!

#### 2 ABSORBERS TO CHOOSE FROM

- H5: 36 kW/cm<sup>2</sup>
- W5: unequalled 100 kW/cm<sup>2</sup>

#### HIGH "POWER TO SIZE" RATIO

6 W continuous reading

#### ENERGY MODE

Measure single shot energy up to 200 J (with the W5 version)

#### SMART INTERFACE

Containing all the calibration data

#### COMPATIBLE STAND

[STAND-S-233](#)

## SPECIFICATIONS

### MEASUREMENT CAPABILITIES

Maximum average power (continuous)	6 W
Maximum average power (1 minute)	7 W
Noise equivalent power <sup>1</sup>	1 mW
Spectral range <sup>2</sup>	0.193 - 20 μm
Typical rise time <sup>3</sup>	0.8 s
Power calibration uncertainty <sup>4</sup>	±2.5 %
Repeatability	±0.5 %

1. Nominal value, actual value depends on electrical noise in the measurement system.
2. For the calibrated spectral range, see the user manual.
3. With anticipation.
4. Including linearity with power.

### MEASUREMENT CAPABILITIES (ENERGY MODE)

Maximum measurable energy <sup>1</sup>	15 J
Noise equivalent energy <sup>2</sup>	0.02 J
Minimum repetition period	4 s
Maximum pulse width	88 ms
Energy calibration uncertainty <sup>3</sup>	±5 %

1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).
2. Nominal value, actual value depends on electrical noise in the measurement system.
3. When single-shot energy calibration is purchased

### DAMAGE THRESHOLDS

Maximum average power density <sup>1</sup>	36 kW/cm <sup>2</sup>
Maximum energy density <sup>2</sup>	1 J/cm <sup>2</sup>

1. At 1064 nm, 10 W CW. May vary with wavelength and average power.
2. At 1064 nm, 7 ns, 10 Hz. Damage thresholds vary with pulse width. Use our Product Finder or contact Gentec-EO to know about damage thresholds for different pulse widths.

### PHYSICAL CHARACTERISTICS

Cooling	Convection
---------	------------

Aperture diameter	17 mm
Absorber	H5
Dimensions	46H x 46W x 10.7D mm
Weight	0.1 kg
<b>ORDERING INFORMATION</b>	
UPI7P-6S-H5-D0	201033
UPI7P-6S-H5-INT-D0	203039
UPI7P-6S-H5-IDR-D0	203327

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

## INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at [gentec-eo.com/contact-us](https://gentec-eo.com/contact-us)