

B3-IR-FILTER

IR filter for BEAMAGE camera.



KEY FEATURES

IR LOW-PASS FILTER

The B3-IR-FILTER is a color glass filter specifically designed for IR applications. Acting as a low-pass filter, the B3-IR-FILTER cuts all the wavelengths below 1250 nm and only lets the IR wavelengths pass. It transmits approximately 70% of the incident light.

READY TO USE WITHIN MINUTES

The B3-IR-FILTER is SM1 threaded and comes with a SM1 to C-mount adaptor so you can mount it on the BEAMAGE camera.

202855

SPECIFICATIONS

MEASUREMENT CAPABILITIES	
Spectral range	1250 - 1350 nm
Parallelism	< 3 arcmin
Maximum power	1 W
Surface quality	80-50 Scratch-Dig
Surface flatness	< \/ 4
Thickness	6.3 mm
DAMAGE THRESHOLDS	
Damage thresholds	30 W/cm2
PHYSICAL CHARACTERISTICS	
Dimensions	30.5Ø X 11.4D mm
Weight	0.04 kg
Mounting thread	SMI
Clear aperture	80% of area
Adaptor included	SM1/C-Mount
Dimensional tolerance	+0.0/-0.2 mm
ORDERING INFORMATIONS	

B3-IR-FILTER

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us