

TUNER

파워 계측용 조율침이 구비된 디스플레이 장치. 단일채널.



제품군 주요 특징

ULTRA-FAST NEEDLE

Less than 1 second response time

READS POWER DETECTORS

Thermopiles and photo detectors of the PH100 and PH20 series

LARGE LCD DISPLAY

- 77 x 58 mm
- 5 mm digits
- Backlight (with AC adaptor)

3 DISPLAY FUNCTIONS FOR THE NEEDLE

- Normal
- Tail (indicates speed)
- Bargraph

Also high and low values hold

SINGLE-BUTTON NAVIGATION

Direct access and long press access to the main functions

LOW CONSUMPTION

Lasts 500 hours with 4 AA alkaline batteries

사양

컨트롤러 및 GUI 사양

디지털 디스플레이 사이즈	77 x 58 mm LCD
데이터 표시	Real time, ultrafast tuning needle: tail, bar graph, high/low
재생률	4 Hz
아날로그 출력	0-1 볼트, 전체 범위, ±1%
외부 트리거	없음
배터리 유형	4 x AA 알칼리
배터리 수명	검출기로 500시간
외부 전원	9 VDC 1.66 A
파워 미터 사양	
파워 범위	10 pW - 10 kW
디지털 해상도	10 pW
모니터 정확성	±1%, 전체 범위
통계	최소 및 최대
응답 시간	최소 및 최대
에너지 미터 사양	
물리적 특성	
치수	210W x 122H x 44D mm
중량	0.47 kg
주문 정보	
TUNER	201207B

이 제품에 관심이 있으십니까?

견적받기

gentec-eo.com/ko/contact-us에서 현지 영업 담당자를 찾으십시오.