

## U-LINK (USB)

PC interface for power & energy measurement. Single-channel, USB output.



### KEY FEATURES

#### THE UNIVERSAL METER

Reads all heads:

- Power: thermopiles, photodetectors and pyroelectrics
- Energy: thermopiles (in single shot mode), photodetectors and pyroelectrics

#### MEASURE FJ ENERGY LEVELS

Thanks to a unique digital method for suppressing the noise on the lower ranges

#### EXTERNAL TRIGGER

Synchronize your U-LINK to your pulsed laser or digital chopper

#### SERIAL COMMANDS

Serial commands are available on both versions to let you take full control

#### REAL-TIME STATISTICAL FUNCTIONS

Max, min, average, standard deviation, RMS and PTP stability

#### SYNCHRONIZE MULTIPLE CHANNELS

With the "SYNC. OUT" port, you can plug multiple U-LINK devices together and create a low-cost multi-channel system.



## SPECIFICATIONS

### CONTROLLER AND GUI SPECIFICATIONS

Digital display size	Computer Screen
Data display	Real Time, Ratio, Line Plot, Histogram, Statistics and 3D Histogram
Analog output	0-2 Volt, Adjustable, Full Scale, $\pm 1\%$
External trigger	3.3 to 12 V
Real-time data transfer	10 kHz
Serial commands via	USB
External power supply	USB 5V, 150 mA

### POWER METER SPECIFICATIONS

Power range	4 pW - 30 kW
Digital resolution	23 bits on current scale
Device accuracy	$\pm 0.5\% \pm 3 \mu V$
Statistics	Current value, max, min, average, standard deviation, RMS & PTP stability, time
Response time	Current value, max, min, average, standard deviation, RMS & PTP stability, time

### ENERGY METER SPECIFICATIONS

Energy range	2 fJ to 30 kJ
Digital resolution	Current Scale/3754
Device accuracy	1% $\pm 50 \mu V$ (< 500 Hz) 2% $\pm 50 \mu V$ (500 Hz - 10 kHz)
Software trigger level	0.1 to 99.9%, 0.1% resolution, default 2%
Repetition rate <sup>1</sup>	10 kHz
Real-time data transfer	10 kHz with time stamp, no missing point
Statistics	Current value, max, min, average, standard deviation, RMS & PTP stability, pulse #, repetition rate and average power

1. Maximum repetition rate may vary with PC and detector speeds.

## PHYSICAL CHARACTERISTICS

Dimensions 57W x 26H x 91D mm

Weight 0.12 kg

## ORDERING INFORMATION

U-LINK (USB) 203510

## INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at [gentec-eo.com/contact-us](https://gentec-eo.com/contact-us)