

PRONTO-10K

Battery type
Battery life

Display size

Display type

Backlight

Display resolution

Portable laser power meter for up to 10000 W.



PRODUCT FAMILY KEY FEATURES

The PRONTO series for high power replaces the FLASH series that is now discontinued. The PRONTO models offer the same laser measurement capabilities, but with new and improved electronics that allow for data logging, more calibration points and USB connection for data transfer and charging the battery.

WIDE POWER RANGE

Very low noise level = wide power range with just one device

NO-WAIT MEASUREMENTS

5 seconds measurements allow for very short cooling time (all models except PRONTO-3K) $\,$

17 hours or 4,200 measurements (with brightness set at 25%)

28.0 x 35.0 mm (128 x 160 pixels)

Touch Screen Color LCD

Adjustable

EASY OPERATION

Color touch screen display

LARGE APERTURE

55 mm aperture to accommodate large beams

RUGGED

- All-metal body
- High damage thresholds

ADVANCED FEATURES

Data logging and data transfer to PC

COMPATIBLE STAND

STAND-S-443

SPECIFICATIONS

MEASUREMENT CAPABILITIES	
Maximum average power	10000 W
Minimum average power	30 W
Noise equivalent power	30 W
Spectral range ¹	0.193 - 20 µm
Power calibration uncertainty	±5 %
Exposure time	5 s
1. For the calibrated spectral range, see the user manual.	
CONTINUOUS POWER MODE	
Response time	5 s
DAMAGE THRESHOLDS	
Maximum average power density ¹	7 kW/cm²
Maximum allowable casing temperature	75 °C
1. At 1064 nm, 6000 W CW. May vary with wavelength and average power.	
CONTROLLER AND GUI SPECIFICATIONS	
Battery type	Rechargeable Li-ion

Internet upgrades via	USB
Data storage	50,000 pts
Battery recharge via	USB
PHYSICAL CHARACTERISTICS	
Aperture diameter	55 mm
Absorber	н
Dimensions	88W x 88L x 46D mm
Weight	2.15 kg
Mounting holes	1 x 8-32, 2 x 1/4-20
ORDERING INFORMATION	
PRONTO-10K	203470

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?



Find your local sales representative at gentec-eo.com/contact-us