

UP19K-50W-W5-D0

Thermal detector for laser power measurement up to 50 W.



PRODUCT FAMILY KEY FEATURES

MODULAR CONCEPT

Increase the power capability of your detector: 5 different cooling modules

VERY HIGH DAMAGE THRESHOLD

100 kW/cm² in average power density

COMPACT DESIGN

Only 21 mm thick (15S model)

ENERGY MODE

Measure single shot energy up to 200 J

SMART INTERFACE

Containing all the calibration data

COMPATIBLE STAND

[STAND-S-233](#)

SPECIFICATIONS

MEASUREMENT CAPABILITIES

Maximum average power (continuous) ¹	50 W
Maximum average power (1 minute) ²	85 W
Noise equivalent power ³	1 mW
Spectral range ⁴	0.193 - 10 μm
Typical rise time ⁵	1.4 s
Power calibration uncertainty ⁶	±2.5 %
Repeatability	±0.5 %

1. Minimum cooling flow 0.5 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.

2. Minimum cooling flow 0.5 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.

3. Nominal value, actual value depends on electrical noise in the measurement system.

4. For the calibrated spectral range, see the user manual.

5. With anticipation.

6. Including linearity with power.

MEASUREMENT CAPABILITIES (ENERGY MODE)

Maximum measurable energy ¹	200 J
Noise equivalent energy ²	0.02 J
Minimum repetition period	5 s
Maximum pulse width	133 ms
Energy calibration uncertainty ³	±5 %

1. For 360 μs pulses. Higher pulse energy possible for long pulses (ms), less for short pulses (ns).

2. Nominal value, actual value depends on electrical noise in the measurement system.

3. When single-shot energy calibration is purchased

DAMAGE THRESHOLDS

Maximum average power density ¹	100 kW/cm ²
Maximum energy density ²	1.1 J/cm ²

1. At 1064 nm, 10 W CW. May vary with wavelength and average power.

2. At 1064 nm, 7 ns, 10 Hz. Damage thresholds vary with pulse width. Use our Product Finder or contact Gentec-EO to know about damage thresholds for different pulse widths.

PHYSICAL CHARACTERISTICS

Cooling	Water
Aperture diameter	19 mm
Absorber	W
Dimensions	76.5H x 50W x 35.5D mm
Weight	0.24 kg

ORDERING INFORMATION

UP19K-50W-W5-D0	200337
UP19K-50W-W5-BLU-D0	203661
UP19K-50W-W5-INT-D0	203049
UP19K-50W-W5-IDR-D0	203357

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us